



Identification data of appropriate **termination**



TERMINATION

<input type="radio"/> For indoor use	<input type="radio"/> Single core	<input type="radio"/> Copper conductor
<input type="radio"/> For external use	<input type="radio"/> Three-core	<input type="radio"/> Aluminium conductor

NOMINAL VOLTAGE

<input type="radio"/> 6 kV (U _{max} 7,2)
<input type="radio"/> 10 kV (U _{max} 12)
<input type="radio"/> 15 kV (U _{max} 17)
<input type="radio"/> 20 kV (U _{max} 24)
<input type="radio"/> 30 kV (U _{max} 36)

CABLE INSULATION

<input type="radio"/> Extruded cable	<input type="radio"/> Full
	<input type="radio"/> Low
<input type="radio"/> Low insulation thickness	
<input type="radio"/> Belted cable	
<input type="radio"/> 3 lead paper	
<input type="radio"/> 1 lead paper with shielded phases	

ARMOUR

<input type="radio"/> Non armoured
<input type="radio"/> Armoured wire
<input type="radio"/> Armoured tape

SHIELD

<input type="radio"/> Copper wire
<input type="radio"/> Copper tapes
<input type="radio"/> Aluminium tube
<input type="radio"/> Lead sheath

CABLE SECTION

<input type="radio"/> 25 mm²
<input type="radio"/> 35 mm²
<input type="radio"/> 50 mm²
<input type="radio"/> 70 mm²
<input type="radio"/> 95 mm²
<input type="radio"/> 120 mm²
<input type="radio"/> 150 mm²
<input type="radio"/> 185 mm²
<input type="radio"/> 240 mm²
<input type="radio"/> 300 mm²
<input type="radio"/> 400 mm²
<input type="radio"/> 500 mm²
<input type="radio"/> 630 mm²

TYPE

<input type="radio"/> Self-shrinking
<input type="radio"/> Heat-shrink

INCLUDES GROUNDING BRAID

<input type="radio"/> Yes
<input type="radio"/> No



INCLUDES CABLE TERMINAL

<input type="radio"/> Yes
<input type="radio"/> No

