KIT IP68

JOINTING BOXES

LOW VOLTAGE



Rav

ech

Electrical performance:

• CEI EN 50393 as applicable • Class 2 in accordance with CEI 64-8.

Gel: UL 94-HB

- **∦** Working temperature: 90°
- **Gel operating temperature:** $-60^{\circ}C / +200^{\circ}C$
- 💥 Fully submersible

Can be used underground

🖉 Halogen-free Gel

Self-extinguishing and resistant to abnormal heat and fire: Glow Wire Flammability Index at +960° C according to EN60695-2-12



MAGIC BOX

IP68 Connection kit complete with Magic Fluid insulating gel.

Universal IP68 kit without shelf life, mechanically robust, non-toxic, suitable for installation even in the most extreme conditions, re-enterable, meeting all international standards. Protects from water, moisture, dust and accidental contact caused by small animals.

ADVANTAGES

- With pre-drilled walls for a faster installation.
- Re-enterable even after long periods of operation.
- Able to absorb external shock without fracturing.
- For installations even at high depths.
- Also suitable for vertical filling.
- No shelf life.
- ► The gel is not-classified as hazardous under the CLP Directive.











PUBLIC LIGHTING

NAVAL SECTOR

OUTDOOR - GARDENS

ELECTRIC GATES

38

Kit box installation sequence



the screws with the

caps.







Install the cable glands. Insert the cables and



connect the wires.

Horizontal installation sequence















PRODUCT / Item	Input cables max. external Ø (mm)	N° and type of cable glands	Box dimensions (mm)
MAGIC BOX 65 MAGICBOX65	22	3 x PG16	Ø 65 x h 35
MAGIC BOX 80 MAGICBOX80	22	3 x PG16	Ø 80 x h 40
MAGIC BOX 100 MAGICBOX100	20	3 x M25 x 1.5	100 x 100 x h 50
MAGIC BOX 120 MAGICBOX120	20	3 x M25 x 1.5	120 x 80 x h 50
MAGIC BOX 150 MAGICBOX150	26	3 x M25 x 1.5	150 x 110 x h 70
MAGIC BOX 190 MAGICBOX190	26	3 x M25 x 1.5	190 x 140 x h 70
MAGIC BOX 240 MAGICBOX240	26	3 x M25 x 1.5	240 x 190 x h 90



Kit complete with cover 3 cable glands Series of closing plugs Insulating gel for complete filling