KIT IP68

LOW VOLTAGE



Rav

ech

Electrical performance: • CEI EN 50393 as applicable • Class 2 in accordance with CEI 64-8.

- Gel: UL 94-HB
- **∬**[■] Working temperature: 90°
- **Gel operating temperature:** $-60^{\circ}C / +200^{\circ}C$
- 💥 Fully submersible
- Can be used underground
- Halogen-free Gel

Self-extinguishing and resistant to abnormal heat and fire: Glow Wire Flammability Index at +960° C according to EN60695-2-12



POWER KIT IP68

The only re-enterable and reusable IP68 kit. Can easily be used for ceiling mounted or recessed applications!

The most versatile, safe solution to fully protect connections in boxes with an IP68 degree of protection. Thanks to *Magic Power*, the newly developed, fast crosslinking, safe and reliable, extremely sticky self-agglomerating gel with very high dielectric, thermal and elastic characteristics, sealing is guaranteed in all type of installation, including submerged. The Power Kit IP68 solution is the only product of its kind! Not only because the insulation can be used in two different ways, both as a traditional "pour" in the box and as a "cross linked and sticky" product (cross linking first), but also because, thanks to its re-enterability and re-usability, it helps you save time and money!

ADVANTAGES

- Magic Power Gel is not-classified as hazardous under the CLP Directive.
- Complete Kit for a perfect connection IP68.
- Insulated with Magic Power Gel the innovative self-amalgamating gel.
- Can also be used in severe environmental conditions.
- Suitable for very high depths.
- No waste.
- No shelf life.



WHERE CAN YOU USE THE **POWER KIT**?

In pools, tanks, submerged pumps, outdoor lighting systems, underground, port piers, marinas, sewer systems, and with temporary connections such as with lights, street vendors, etc.

HOW DO YOU USE THE **POWER KIT**?

The insulation can be poured into the box (Pour!) or, for special applications, cross linked in the measuring jug and applied around the connection (Stick!). Mix the Magic Power gel in a 1:1 ratio in the supplied measuring jug. The gel will cross link in less than 15 minutes.

NO WASTE

The cross linked gel which remains on the bottom after mixing can be easily removed from the jug and saved for later use.

40

Chose the **POUR** or **STICK** method most suited for your needs



You can use the Magic Power gel supplied in the two-component bottle in a 1:1 ratio by simply pouring it after mixing into the box supplied in the kit, to protect and seal internal connections. The gel cross links in just 15 minutes, but the box can be energised immediately.

RE-ENTER AND RE-USE







Thanks to Magic Power Gel, the box can be **re-opened**, **inspected** and **re-insulated** all using the original installed product.

STICK



Pour the components in the measuring jug, mix and leave to cross link (about 15 minutes). Remove the insulation and position it in small parts around the connection so that it is fully covered. Insulation saved from previous mixes can of course be utilised.

IN A HURRY? ADVERSE WEATHER CONDITIONS? PREPARE YOUR







LOW VOLTAGE





Ray Tech



WHAT ARE THE ADVANTAGES TO USING THE **POWER KIT**?

- The insulation is extremely sticky and self-amalgamating, with no shelf life, it is non-toxic and it adheres to everything while leaving your hands clean and dry.
- The kit does not cause waste: insulation left over in themeasuring jug can be saved for later use.
- Re-enterable and reusable, saving time and money.
- The supplied box has pre-marked holes.

• Compatible with Magic Gel.

- A slight exothermic reaction (temperature increase of about 3°C) speeds up cross linking in cold weather conditions.
- Even protects boxes mounted on the ceiling to IP68 if using the "stick" method. Could also use left over product from previous installations.
- Insulation can be pre-prepared: at home, at work or in your car and then applying it once cross linked, saving time when you're in a hurry or in adverse weather conditions.

SOME LEFT OVER? SAVE IT!





Left over gel that has already cross linked can be easily removed from the measuring jug and saved for later use.







PRODUCT / Item	Box	Insulating filler
POWER KIT 65	Ø 65 x h 35 mm	Single two-component bottle
POWER-65	+ 2 cable glands PG16 / caps	1 small jug - 1 spatula in wood
POWER KIT 80	Ø 80 x h 40 mm	Single two-component bottle
POWER-80	+ 3 cable glands PG16 / caps	1 small jug - 1 mixing spatula
POWER KIT 100	100 x 100 x h 50 mm	Single two-component bottle
POWER-100	+ 3 cable glands M25 x 1,5 / caps	1 small jug - 1 mixing spatula
POWER KIT 120	120 x 80 x h 50 mm	Single two-component bottle
POWER-120	+ 3 cable glands M25 x 1,5 / caps	1 small jug - 1 mixing spatula